Appl. No. 10/030,448

Amdt. dated June 21, 2006

Reply to Office action of February 21, 2006

In the Claims:

Claims 1--12 were present. Claims 1--3 and 8--12 are canceled. Claims 4--7 are allowed.

- 1. (canceled)
- 2. (canceled)
- (canceled)
- 4. (previously presented) A speaker comprising:
- a magnetic circuit having a center magnetic pole and an air gap;
- a voice coil wound around a voice coil bobbin disposed in the air gap of the magnetic circuit;
 - a frame mounted onto the magnetic circuit;
- a cone-shaped diaphragm made from foamed resin and disposed between the frame and the one end of the voice coil bobbin;
- a support mounted on the center magnetic pole of the magnetic circuit including an induction coil wound around the support; and
- at least one light source held in a holder secured to the end of the support for directing light onto the cone-shaped diaphragm by being energized by the voltage induced in the induction coil.

Appl. No. 10/030,448

Amdt, dated June 21, 2006

Reply to Office action of February 21, 2006

5. (previously presented) A speaker of claim 4, wherein the holder is configured to hold a plurality of light emitting

diodes (LEDs) directed to illuminate the cone-shaped diaphragm in

radial manner.

6. (previously presented) A speaker of claim 4, wherein

the light source is controlled to emit light of different color

depending on the audio signal to be applied to the voice coil.

7. (previously presented) A speaker of claim 5, wherein

the light source is controlled to emit light of different color

depending on the audio signal to be applied to the voice coil.

8. (canceled)

9. (canceled)

10. (canceled)

11. (canceled)

12. (canceled)

Page 3 - RESPONSE (U.S. Patent Appln. S.N. 10/030,448) [\\Files\files\Correspondence\June 2006\v190rtoa062106.doc]